



The IWP-12 delivers a stylish and graphically-rich control solution. A 12" LCD, 1024 x 768 display, featuring 24-bit color depth (2.4 million colors) makes this the ideal interactive user-interface for home automation, browsing the Internet, streaming multimedia, intercom, and more. NavNet touch panels eliminate the stacks of remote controls, hard to use audio keypads and the clutter of wall switches, thermostats and security keypads. This both simplifies and expands the ability to control a broad range of the homes systems and devices.

Touch Panel Specifications

Connectors & Expansion

One (1) 10/100/1000BaseT Gigabit, auto-negotiating network port

Two (2) proprietary USB expansion ports

One (1) DB-9 male, service port (not usable by end user)

One (1) DE-15 female, service port (not usable by end user)

One (1) DIN-7 female, service port (not usable by end user)

One (1) power connector

Power Requirements

Power Supply - 100-240 Volts AC, 50/60 Hz, 1.5 Amps (AC line input)

Touch Panel - 12 Volts DC, 4.17 Amps, 50 watts (DC power supply to controller)

Environmental

Temperature: 41° to 113°F (5° to 45°C)

Humidity: 10% to 90% RH (non-condensing)

Enclosure

Chassis: Steel

Faceplate: Acrylic, black, high-gloss finish

Mounting: Requires NavNet IWP-12WB pre-construction wall box enclosure or IWP-12PCMB pre-construction mounting bracket

Dimensions

Touch Panel

Height: 9.75 in (24.8 cm)

Width: 13.75 in (35.0 cm)

Depth: 2.25 in (5.8 cm)

Cutout

Height: 9.75 in (24.8 cm)

Width: 12.5 in (31.8 cm)

Weight

6.2 lb (2.8 kg)

Warranty

One (1) year manufacturers' limited parts and labor



NavNet™
FOR CONTROL FREAKS™